

Amendments to the Claims:

Please amend claims 1, 11, 14, 15, 17, 18, 23, 25-29, and 39, and please add new claims 46-66 as follows.

This listing of claims replaces all prior versions, and listings, of claims in the application.

Listing of claims:

1. (Currently amended) A partition mount for mounting between a pole and an abutting surface comprising:
 - a pole interface ~~coupled to~~on a mount body, the pole interface adapted for interfacing with a side portion of a pole;
 - a head interface ~~coupled to~~on the mount body; and
 - a biasing unit ~~[[for]]~~that outwardly ~~biasing~~biases the pole interface and head interface with respect to each other, such that relative positions of the pole interface and the head interface can be varied.
2. (Original) The partition mount of claim 1 wherein the pole interface is at a first end of the mount body and wherein the head interface is at a second end of the mount body.
3. (Original) The partition mount of claim 1 wherein the pole interface comprises a C-shaped body.
4. (Original) The partition mount of claim 1 wherein the pole interface comprises a non-skid material.
5. (Original) The partition mount of claim 1 wherein the head interface comprises a clamp that is adapted for coupling the partition mount to a head.
6. (Original) The partition mount of claim 5 wherein the head comprises a pad.

7. (Original) The partition mount of claim 6 wherein the pad comprises a non-skid material.
8. (Original) The partition mount of claim 6 wherein the pad comprises a compressible material.
9. (Original) The partition mount of claim 6 wherein the pad is elongated.
10. (Original) The partition mount of claim 6 wherein the pad provides a point of contact.
11. (Currently amended) The partition mount of claim 5 wherein the head interface is integral with the mount body.
12. (Withdrawn) The partition mount of claim 1 wherein the head interface comprises one of a ball and socket.
13. (Withdrawn) The partition mount of claim 1 wherein the mount body, head interface, and pole interface are configured along a common axis.
14. (Currently amended) The partition mount of claim 1 wherein the mount body comprises first and second arms coupled by a hinge, and wherein the pole interface is ~~coupled to~~on the first arm and the head interface is ~~coupled to~~on the second arm.
15. (Currently amended) The partition mount of claim 14 wherein the first arm is C-shaped and includes the pole interface at a first end and a ~~[[first]]~~leverage handle at a second end.
16. (Original) The partition mount of claim 15 wherein the first arm further includes a wall interface of non-skid material between the first end and the second end.

17. (Currently amended) The partition mount of claim 14 wherein the second arm is L-shaped and includes the head interface at a first end and a ~~second~~ grip handle at a second end.
18. (Currently amended) The partition mount of claim 17 wherein the second arm includes a hinge such that the head interface and ~~second~~ grip handle can be positioned relative to each other at a range of angles.
19. (Original) The partition mount of claim 1 wherein the biasing unit comprises a spring.
20. (Original) The partition mount of claim 19 wherein the spring is one of inwardly biased and outwardly biased.
21. (Withdrawn) The partition mount of claim 1 wherein the biasing unit comprises at least one of a ratcheting mechanism and a manually operated screw.
22. (Original) The partition mount of claim 1 further comprising a wall interface coupled to the mount body.
23. (Currently amended) The partition mount of claim ~~[[1]]~~ 22 wherein the wall interface comprises non-skid material.
24. (Original) The partition mount of claim 1 wherein the mount body comprises a material selected from the group consisting of plastic, graphite, wood, and aluminum alloy.
25. (Currently amended) A partition mount for mounting between a pole and an abutting surface comprising:
 - a mount body ~~comprises~~ comprising first and second arms coupled by a hinge;
 - a pole interface ~~coupled to~~ on the first arm, the pole interface adapted for

interfacing with a side portion of a pole;

a head interface ~~coupled to~~on the second arm[.]; and

a biasing unit ~~that~~for ~~that~~outwardly biasing ~~biases~~biases the pole interface and head interface with respect to each other, such that relative positions of the pole interface and the head interface can be varied.

26. (Currently amended) The partition mount of claim 25 wherein the first arm is C-shaped and includes the pole interface at a first end and a ~~[[first]]~~leverage handle at a second end.
27. (Currently amended) The partition mount of claim ~~[[25]]~~26 wherein the first arm further includes a wall interface of non-skid material between the first end and the second end.
28. (Currently amended) The partition mount of claim 25 wherein the second arm is L-shaped and includes the head interface at a first end and a ~~second~~ grip handle at a second end.
29. (Currently amended) The partition mount of claim 28 wherein the second arm includes a hinge such that the head interface and ~~second~~ grip handle can be positioned relative to each other at a range of angles.
30. (Original) The partition mount of claim 25 wherein the biasing unit comprises a spring.
31. (Original) The partition mount of claim 25 wherein the pole interface comprises a C-shaped body.
32. (Original) The partition mount of claim 25 wherein the pole interface comprises a non-skid material.

33. (Original) The partition mount of claim 25 wherein the head interface comprises a clamp that is adapted for coupling the partition mount to a head.
34. (Original) The partition mount of claim 33 wherein the head comprises a pad.
35. (Original) The partition mount of claim 34 wherein the pad comprises a non-skid material.
36. (Original) The partition mount of claim 34 wherein the pad comprises a compressible material.
37. (Original) The partition mount of claim 34 wherein the pad is elongated.
38. (Original) The partition mount of claim 34 wherein the pad provides a point of contact.
39. (Currently amended) The partition mount of claim 33 wherein the head interface is integral with the mount body.
40. (Withdrawn) The partition mount of claim 25 wherein the head interface comprises one of a ball and socket.
41. (Original) The partition mount of claim 33 wherein the head is integral with the head interface.
42. (Original) The partition mount of claim 25 wherein the biasing unit comprises a spring.
43. (Original) The partition mount of claim 42 wherein the spring is one of inwardly biased and outwardly biased.

44. (Withdrawn) The partition mount of claim 25 wherein the biasing unit comprises at least one of a ratcheting mechanism and a manually operated screw.
45. (Original) The partition mount of claim 25 wherein the mount body comprises a material selected from the group consisting of plastic, graphite, wood, and aluminum alloy.
46. (New) A partition mount for mounting between a pole and an abutting surface comprising:
a pole interface coupled to a mount body, the pole interface adapted for interfacing with a side portion of a pole;
a head interface coupled to the mount body, the head interface comprising a clamp that is adapted for coupling the partition mount to a head, the head comprising a pad; and
a biasing unit for outwardly biasing the pole interface and head interface with respect to each other.
47. (New) The partition mount of claim 46 wherein the pad comprises a non-skid material.
48. (New) The partition mount of claim 46 wherein the pad comprises a compressible material.
49. (New) The partition mount of claim 46 wherein the pad is elongated.
50. (New) The partition mount of claim 46 wherein the pad provides a point of contact.
51. (New) A partition mount for mounting between a pole and an abutting surface comprising:
a mount body comprising first and second arms coupled by a hinge;
a pole interface coupled to the first arm, the pole interface adapted for interfacing with a side portion of a pole, the first arm being C-shaped and including the pole interface

at a first end and a leverage handle at a second end;
a head interface coupled to the second arm; and
a biasing unit for outwardly biasing the pole interface and head interface with respect to each other.

52. (New) The partition mount of claim 51 wherein the first arm further includes a wall interface of non-skid material between the first end and the second end.

53. (New) A partition mount for mounting between a pole and an abutting surface comprising:
a mount body comprising first and second arms coupled by a hinge;
a pole interface coupled to the first arm, the pole interface adapted for interfacing with a side portion of a pole;
a head interface coupled to the second arm, the second arm being L-shaped and including the head interface at a first end and a grip handle at a second end; and
a biasing unit for outwardly biasing the pole interface and head interface with respect to each other.

54. (New) The partition mount of claim 53 wherein the second arm includes a hinge such that the head interface and grip handle can be positioned relative to each other at a range of angles.

55. (New) A partition mount for mounting between a pole and an abutting surface comprising:
a pole interface coupled to a mount body, the pole interface adapted for interfacing with a side portion of a pole;
a head interface coupled to the mount body;
a wall interface coupled to the mount body; and
a biasing unit for outwardly biasing the pole interface and head interface with

respect to each other.

56. (New) The partition mount of claim 55 wherein the wall interface comprises non-skid material.
57. (New) A partition mount for mounting between a pole and an abutting surface comprising:
 - a mount body comprising first and second arms coupled by a hinge;
 - a pole interface coupled to the first arm, the pole interface adapted for interfacing with a side portion of a pole;
 - a head interface coupled to the second arm, the head interface comprising a clamp that is adapted for coupling the partition mount to a head, the head comprising a pad; and
 - a biasing unit for outwardly biasing the pole interface and head interface with respect to each other.
58. (New) The partition mount of claim 57 wherein the pad comprises a non-skid material.
59. (New) The partition mount of claim 57 wherein the pad comprises a compressible material.
60. (New) The partition mount of claim 57 wherein the pad is elongated.
61. (New) The partition mount of claim 57 wherein the pad provides a point of contact.
62. (New) A partition mount for mounting between a pole and an abutting surface comprising:
 - a mount body comprising first and second arms coupled by a hinge;
 - a pole interface coupled to the first arm, the pole interface adapted for interfacing with a side portion of a pole;

a head interface coupled to the second arm, the head interface comprising a clamp that is adapted for coupling the partition mount to a head, the head being integral with the head interface; and

a biasing unit for outwardly biasing the pole interface and head interface with respect to each other.

63. (New) A partition mount for mounting between a pole and an abutting surface comprising:

a mount body comprising first and second arms coupled by a hinge;

a pole interface coupled to the first arm, the pole interface adapted for interfacing with a side portion of a pole;

a head interface coupled to the second arm; and

a biasing unit for outwardly biasing the pole interface and head interface with respect to each other.

64. (New) The partition mount of claim 63 wherein the spring is one of inwardly biased and outwardly biased.

65. (New) A partition mount for mounting between a pole and an abutting surface comprising:

a mount body comprising first and second arms coupled by a hinge;

a pole interface coupled to the first arm, the pole interface adapted for interfacing with a side portion of a pole, the first arm being C-shaped and including the pole interface at a first end and a leverage handle at a second end, and a wall interface of non-skid material between the first end and the second end;

a head interface coupled to the second arm, the second arm being L-shaped and including the head interface at a first end and a grip handle at a second end; and

a biasing unit for outwardly biasing the pole interface and head interface with respect to each other.

66. (New) The partition mount of claim 28 wherein the second arm includes a hinge such that the head interface and grip handle can be positioned relative to each other at a range of angles.